tzuba vision
ECO Light Systems Ltd

INBAR2

Street Light

Optimum style, superior performance. Powered with Bridgelux COB, Inbar street light series offers a comprehensive line of high efficiency street LED lighting solutions. The innbar series provides variety of six powerful options for any street illumination needs starting from a a trail up to a wide highway! Inbar series complies with the highest standards, such as ZHAGA, Photobiological and most of safety standards.
Inbar series are supplied with a variety of asymmetrical and symmetrical tempered lenses such as polariz and anti-glare treatment.

heavy duty lighting
water resistant IP66

Specifications

LED SSL	Bridgelux USA Vero - 18 x 2
FLUX INTENSITY	12,600 lumen
OVERALL EFFICIENCY	140 lm/w
CRI	70-90% (selectable)
LENS	cristal, tempered anti pollutuion lens
LIGHT ANGLE	selectable: 135x75, 120x120 degrees anti glare, polarized
COLOR TEMP	selectable: 3000k, 3500k, 4000k, 5000k

Electrical Specifications

DRIVER	MEANWELL Constant Current
INPUT VOLTAGE	90-240 V
INPUT CURENT	0.5 A (230v)
POWER FACTOR	>0.98
POWER	100 watt

Technical Specifications

WEIGHT	4.5 kg
MATERIAL	ADC12 - thermal aluminum
SIZE	280x720x72 mm

EQUIVALENT: HPS 150-250w, energy save: up to 85%
WARRANTY : 3 years, 10 years for the ssl (led chip)
STANDARDS: SII Quality Standard Certification, IP 66 ,ZHAGA, LM80, iec61347, Photobiological Certification,

TzubaVision Eco Light Systems Ltd - Tzuba 908700, ISRAEL - Tel 02-9967001
Web: www.tzubavision.co.il Mail: info@tzubavision.co.il